Mixed-Signal IC

Creating a Mixed-Signal World



FIG. 1A

Antrim's Synthesis Methodology



FIG. 1B

Major Components of Antrim-MSS

Synthesis Library



- Simulation models in Verilog-A/MS
  - represent library functions, parameterized to user's performance specifications
- Characteristic functions of design parameters
  - model circuit performance behavior during optimization
- Test harnesses and characterization plans
  - developed with Antrim-ACT
- Netlists of mixed-signal functions
  - working circuits, parameterized for sizing to achieve user's performance specifications
- Process technology files - models and design rules
- Synthesizable layout cells

FIG 1C

Major Components of Antrim-MSS

Synthesis Toolset



- Antrim-MSS Command Interpreter
  - extensions to Perl scripting language for synthesis plan execution
- Optimizers
  - toolkit of algorithms for sizing of design parameters
- Antrim-AMS
  - for simulation of characteristic functions, behavioral models and sized netlists
- Antrim-ACT
  - for development of characteristic functions, analytical models, test harnesses, circuit characterization
- Parasitic calculators
  - layout parasitic estimation from process rules and sized netlists
- Layout generators

FIG. 1D

Major Components of Antrim-MSS

Synthesis Plans

- Blueprints for the successful synthesis of mixed-signal IP



- Developed by expert mixed-signal IC designers using MSS and ACT plan development tools
- Programmed series of steps for circuit partitioning, model selection, sizing and optimization
- Specifications of design parameters to be used as optimization variables
- Specifications of performance characteristics to be used as optimization goals
- Steps for process retargeting
- Antrim-ACT characterization plan
    - Experiments
    - Test harnesses
    - Stimuli and other controls

FIG. 1E

Plan Author

Design Flow

- Design Partitioning
- Characterization
- Model Development
  - circuit
  - behavioral
  - analytic
- Setup Performance Parameters
  - measurements
  - tests harnesses
- Set Design Parameters
- Define Optimization Steps

FIG. 1F

Plan User

Design Flow

- Select Function
- Specify Process
- Performance Specification
- Execute Plan
- Verification of Results

FIG. 1G

Antrim-MSS Architecture



FIG. 2

Development of a Synthesizable VCO

- Circuit features:
  - Three cells: bias generator, differential delay cell, level restore
  - Eight delay stages for 100 MHz - 200 MHz operation
- Performance parameters:
  - power
  - center frequency
- Optimization plan:
  - size delay cell and bias circuit to achieve user❼s specifications



FIG. 3

Cost Function

- User-specified performance specs are formulated into a single cost function
- Optimization seeks a zero cost solution



Fig 4A

Cost Function





FIG 4B

Cost Function



FIG. 4C

Cost Function





FIG. 4D

Example: Synthesis Plan for a VCO

Step One

- Size bias transistor for power specification
- 1st step - budget power according to user specification

  $P_{tot} = P_{bias} + 8*P_{delay}$
- NMOS transistor must remain in triode region with $V_{ds} = V_{diode}$
- Minimize W_{bias} & L_{bias} to meet spec



FIG. 5

Example: Synthesis Plan for a VCO

Step Two

- Mirror NMOS transistors from bias cell
- Size delay cell transistors for frequency spec
- Use behavioral model of F_0 vs. $W_{diff/}$,L_{diff}
- Minimize diff. pair for input load in ring oscillator
- Set L_{diff} to L_{min}
- Optimize W_{diff}



FIG. 6

Example: Synthesis Plan for a VCO

Step One

- Size bias transistor for power specification
- Measure current with condition $V_{ds} = V_{diode}$
- Minimize W_{bias} & L_{bias} to meet spec
- Analysis Setup:
  - simulate nbias_ivdc.v
    - test harness for bias current sizing
  - analysis = bias.tst
    - measurement experiment for current



FIG. 7


Family of Curves for Fmin
x 10^8
1.8
1.6
1.4
1.2
1
0.8
0.6
0.4
0.2
Fmin(wd) @ lb,wb
810
800
830
820
860
890
VCO frequency characteristics

FIG. 8.

Example: Synthesis Plan for a VCO

partitioning design



FIG. 9

Example: Synthesis Plan for a VCO

Step One



Fig 10

Example: Synthesis Plan for a VCO

Step Two



FIG 11

Example: Synthesis Plan for a VCO

Finish Steps



FIG. 12

Synthesis Plan for a VCO

Finish Steps

- Size noncritical MOSFETs in current sources
  - doesn't require optimization
- Synthesize level translator
- Verify complete design
- Could add other performance specifications
  - gain
  - F_{min}
  - F_{max}

FIG 13